

DEMASLED

1	
2	
3	
(ECR)	

Electronic Data


Parameter	Units	Min.	Rated	Max.	Remark
Supply Voltage	V	10,8	12	13,2	12 VAC/DC
Supply Frequency	Hz				
Supply Current	mA	149	165	182	182
Power Consumption	W	1,7	2	2,3	
Power Factor	-	0,9			
Drive output voltage	V		6		
Drive output current	mA	261	290	319	

LED Data

LED Quantity	-	2PCS	
LED Vendor	-		

Chromaticity Data


Parameter	Units	Min.	Rated	Max.	Remark
Luminous Flux	lm	144	160		1
Max Luminous Intensity	cd	293	325		
Beam Angle	°	30	36	42	0.5 lmax; 0.1 lmax
Luminous Efficiency	lm/W	72	80		
CRI	-	80			
CCT	K	2870	3000	3220	
SCDM	-			6	ANSI
Energy Efficiency Index (EEI)	-		0,11		A++
Light Distribution Curve					



## Operating Condition

Parameter	Units	Min.	Rated	Max.	Remark
Operating Ambient Temperature	℃	-20	25	40	
Rated Lamp Life	H		2500		25℃,L70,F50
Starting Time	s			0,5	
Lamp Warms-up time to 60%	s			1	
Lamp Warms-up time to 95%	s			1	

## Structure Data

Parameter	Units	Min.	Rated	Max.	Remark
Weight	g	10.20	12	13.80	
Base Type	-	GU4			
	-				
Drawings	mm				

## Product Certificate

Standards	<input type="checkbox"/> IEC62560及其等效标准	<input type="checkbox"/> IEC62612及其等效标准	<input type="checkbox"/> UL1993+UL8750		
	<input checked="" type="checkbox"/> CISPR15及其等效标准	<input checked="" type="checkbox"/> IEC62471	<input type="checkbox"/> FCC 47 part 15		
	<input checked="" type="checkbox"/> IEC61000-3-2/3及其等效标准	<input checked="" type="checkbox"/> No 1194/2012(ErP)	<input type="checkbox"/> 其它		
	<input checked="" type="checkbox"/> IEC61547及其等效标准				
Certificates	<input checked="" type="checkbox"/> CE	<input type="checkbox"/> EST	<input type="checkbox"/> ENCE	<input type="checkbox"/> PROCEL	<input type="checkbox"/> NOM

Other Requirements	ROHS
--------------------	------